



MF2555, MF3555

SIMPLICITY, SAFETY AND SUSTAINABILITY

The A3 color multifunction printers, d-Color MF2555 and MF3555, are designed for modern work environments that demand high reliability, quality, and safety standards. Featuring a user-friendly 10.1-inch color touch-sensitive panel with a modern interface, printing is simple and efficient.

These printers offer a diverse range of scanning options, including a rapid single-pass duplex scanning feeder capable of scanning up to 200 pages per minute. With various finishing options, they ensure optimal productivity. The printer's exceptional image quality and versatile finishing choices enable the seamless completion of complex tasks with guaranteed quality.

Complying with the latest security requirements, the d-Color MF2555-MF3555 incorporate high-level integrated features to protect sensitive data and secure the device against potential cyber threats. Standard security protocols such as S/MIME for digital signatures, SCEP for simplified certificate registration, OCSP/CRL for certificate revocation status checks, and TLS 1.3 for secure internet communication have been added to the Data Security Kit and the TPM for data encryption.

Additionally, these printers result from informed research focused on minimizing environmental impact. The reduction of CO2 emissions is ensured through low energy consumption and particularly low TEC values. The use of toner and long-lasting components helps control operating costs and significantly reduces waste.

Colour Multifunction Digital Systems

COLOUR	
SPEED	
QUALITY	
COLOUR TOUCH SCREEN	
ECO-FRIENDLY	
NETWORK	
SECURITY	
MOBILITY AND CLOUD	
WI-FI AND WI-FI DIRECT	

* optional



SPECIFICATIONS

GENERAL

Technology: colour laser with the Jaws development platform to customise the system

Operation panel: 10.1" colour touch display, speakers for job notifications, can be tilted from 15° to 90°

Print Speed: d-Color MF2555 up to 25 A4 pages and 12 A3 pages per minute; d-Color MF3555 up to 35 A4 pages and 17 A3 pages per minute in colour and black and white.

Print Speed/duplex printing: d-Color MF2555 up to 25 A4 pages; d-Color MF3555 up to 35 A4 pages and 17 A3 pages per minute

Resolution: 4,800 dpi equal to 1,200 dpi (printing); 600 × 600 dpi (scanning/copying)

Warm-up time: 18 seconds maximum

First print out time: d-Color MF2555 7 seconds max. for B&W and 9.2 seconds for colour; d-Color MF3555 5.9 seconds for B&W and 7.7 seconds for colour;

First copy time: d-Color MF2555 7.4 seconds max. for B&W and 9.8 for colour (from the document feeder), 6.4 seconds max. for B&W and 8.5 for colour (from the platen glass); d-Color MF3555 6.3 seconds max. for B&W and 8.5 for colour (from the document feeder), 5.3 seconds max. for B&W and 7.0 for colour (from the platen glass)

Processor: ARM A53 (Quad Core) 1.6 GHz

Memory: standard 4 GB, 32 GB SSD, optional 320 GB or 1 TB HDD

Interfaces: standard interface USB 3.0 (high speed), 4 x USB Host Interface, Gigabit Ethernet (10BaseT/100BaseTX/1000BaseT, IPv6, IPv4, IPSec, 802.3az support), Wi-Fi optional (IEEE 802.11a/b/g/n/ac), 2 slot eKUIO for internal printer server optional or for Fax System optional, slot for Wireless LAN optional, slot for SD card optional, NFC tag

Dimensions (L x D x H): 602 mm × 665 mm × 790 mm

Weight: approximately 90 kg

Power supply: AC 220-240 V, 50/60 Hz

Energy Consumption during Copying/Printing:

d-Color MF2555 450 W; d-Color MF3555 590 W;

Energy saving mode:

Ready mode: 40 W

Sleep mode: 0.5 W

Noise levels (sound pressure level ISO 7779 measured at a distance of 1 metre):

Colour Printing/Copying: d-Color MF2555 48.0 dB(A) LpA; d-Color MF3555 49.0 dB(A) LpA

Stand-by: d-Color MF2555 31.4 dB(A) LpA; d-Color MF3555 31.3 dB(A) LpA

TEC (Typical Power Consumption): d-Color MF2555 0.31 kWh/week; d-Color MF3555 0.44 kWh/week (according to ENERGY STAR 3.0)

Safety standards: TÜV/GS, CE.

These products are manufactured by a company that operates in accordance with ISO 9001 quality standards and ISO 14001 environmental standards.

INPUT PAPER CAPACITY

All paper capacities shown are based on a maximum paper thickness of 0.11mm under normal environmental conditions.

Input paper capacity: multi-use bypass: 150 sheets, 52-300 g/m², Banner 136-163 g/m², A6R-SRA3 (320 x 450 mm), Banner max. 304.8 x 1,220 mm; standard tray: 2 x 500 sheets, 52-300 g/m²; upper tray from A6R to A4R, lower tray from A6R up to SRA3

Maximum paper input paper capacity with optional accessories: 7,150 A4 sheets

Duplex printing standard: supports weights of 60 to 256 g/m², A6R up to SRA3

Output paper capacity standard: 500 sheets, face down, maximum 5,000 sheets with options.

PRINTER

Emulations: PCL6 (PCL5c/PCL-XL), KPDL3 (PostScript 3 compatible), PDF Direct Print, XPS Direct Print and OpenXPS.

Operating Systems: all current Windows operating systems, MAC OS X 10.9 or later, Unix, Linux, and other operating systems on request

Fonts/barcodes: (PCL6) 93 downloadable fonts, (KPDL 3) 136 fonts, (Calibri) 4 fonts, (Cambria) 4 fonts, 1 Bitmap font, 45 types of one-dimensional barcodes, 1 type of twodimensional barcode (PDF417)

Printing features: direct print encrypted PDF 2.0, print e-mail, WSD printing, SSL secure printing, IPsec, SNMPv3, fast copying, proof and hold, confidential printing, job memorisation and job management functions.

Printing from supported mobile device: Olivetti Mobile Print App for iOS and Android, AirPrint®, NFC, Wi-Fi Direct (optional)

COPIER

Max. format of original: A3/Ledger

Continuous copying: 1-9,999

Zoom: 25-400 % with increments of 1 %

Predefined magnification ratios: 5R/ 5I

Exposure method: manual: 17 levels

Image regulation: Text + Photo, Photo, Text, Diagram/Map

Features: one scan for multiple copies, electronic collation, 2 in 1, 4 in 1, image repeat, numbering, cover mode, booklet copy, interrupt copy, form overlap, margin shift, automatic tray selection, skip blank page, copy of identity card, erase writing and highlighter markings

SCANNER

Features: Scan-to-email, Scan-to-FTP, Scan-to-SMB 3.0, Scan-to-USB Host, Scan-to-box, Network TWAIN, Scan to WSD (WIA Driver Network)

Scan speed: up to 200 ipm (300 dpi, A4, duplex, with DP-7160/DP-7170)

Scanning resolution: 600, 400, 300, 200 dpi, 256 level grayscale

Maximum scanning format: A3, Ledger

Identifying originals: Text, Photo, Text + Photo, light text/ fine lines, optimised for ORC

File types: TIFF, PDF, PDF/A, JPEG, Open XPS, compressed

PDF, hyper-compressed PDF, PDF/A-1a/b, PDF/A-2a/b/u, searchable PDF (optional), MS Office files (optional)

FAX (OPTIONAL)

Compatibility: ITU-T Super G3

Modem speed: 33.6 kbps max.

Transmission time: 3 seconds max. (JBIG)

Scanning speed: 2 seconds max.

Max. format of original: A3/Ledger, Banner up to 1,600 mm Compression method: JBIG, MMR, MR, MH

Features: network fax, rotation transmission and reception, duplex transmission and reception, encrypted transmission and reception, memory reception, mailbox, remote diagnostics, polling transmission and reception, broadcast, optional internet fax, dual fax line with second Fax System 12

CONSUMABLES

Average toner life is based on A4-size pages, continuous printing and 5% coverage

Black toner: d-Color MF2555 up to 25,000 A4 pages; d-Color MF3555 up to 30,000 A4 pages

Toner colours (Cyan, Magenta, Yellow):

d-Color MF2555 up to 12,000 A4 pages; d-Color MF3555 up to 20,000 A4 pages

Staple cartridge: SH-10, 3 cartridges with 5,000 staples, for DF-7100 and DF-7120; SH-12, 3 cartridges with 5,000 staples, for DF-7140

WT-8500 waste toner box: 40,000 sheets (5% coverage of original calculated as B&W, colour = 7:3)

OPTION

UG-36: License to increase device speed to 35 ppm

Fax System 12

Internet Fax Kit (A) AC

Scan Extension Kit (A) AC: searchable PDF scan (OCR integrated), conversion to PDF or MS Office e (docx, xlsx, pptx)

Platen cover type (E)

DP-7140 Automatic document feeder: (with inversion), 50 sheets, 45-160 g/m² (one side only), 50-120 g/m² (duplex), A5R-A3, banner up to 1,900 mm

DP-7150 Automatic document feeder: (with inversion), 140 sheets, 35-160 g/m² (one side only), 50-120 g/m² (duplex), A6R-A3, banner up to 1,900 mm

DP-7160 Automatic document feeder: (duplex scanning), 320 sheets of 50-80 g/m², 35-220 g/m² (one side only), 50-220 g/m² (duplex), A6R-A3, banner up to 1,900 mm

DP-7170 Automatic document feeder: (duplex scanning with ultrasonic sensors), 320 sheets of 50-80 g/m², 35-220 g/m² (one side only), 50-220 g/m² (duplex), A6R-A3, banner up to 1,900 mm DT-730B): document tray

CB-7210M: metal copy desk

PF-7140 Trays: 2 x 500 sheets, 52-300 g/m², A6R-SRA3

PF-7150: 2 x 1,500 sheets, A4, 52-300 g/m², A4, B5, Letter

PF-7170 Large-capacity trays: 2 x 1,500 sheets, A4, 52-300 g/m², A4, B5, Letter

PF-7120 Large-capacity side tray: 3,000, A4 sheets, 60-300 g/m²

DF-7100 Internal finisher: 500 A4 sheets, 52-300 g/m², A6R-SRA3 Stapling up to 50 A4 sheets or 30 A3 sheets, 3 positions

PH-7120 Internal punch kit: for DF-7100 internal finisher

PH-7130 Internal punch kit: for DF-7100 internal finisher (Swedish type)

DF-7120 Staple finisher: 1,000 A4 sheets, 52-300 g/m², A6R-SRA3, stapling up to 50 A4 sheets or 30 A3 sheets, 3 positions

DF-7140 Staple finisher: main tray: 4,000 A4 sheets, secondary tray, 200 A4 sheets, 52-300 g/m², A6R-SRA3, Stapling up to 65 A4 sheets or 30 A3 sheets, 3 positions

AK-7110 Relay unit: for the Finishers DF-7120 and DF-7140.

PH-7C Punch kit: for DF-7120 and DF-7140, 2-hole/4-hole, 45-300 g/m², A5R-A3

PH-7D Punch kit: for DF-7120 and DF-7140, 2-hole/4-hole, 45-300 g/m², A5R-A3 (Swedish type)

MT-730 (B) Job Separator Tray for DF-7140: 7 compartments for 100 A4 sheets, 50 A3/B4 sheets, 60-163 g/m²

BF-730 booklet unit and triple fold for DF-7140: Fold in half 52-256 g/m², A3, B4, A4R, Booklets: 20 sheets max.

(64 pages, 60-90 g/m²), Fold with no staples: 5 sheets max. (60-90 g/m²), Triple fold: 5 sheets max. (60-120 g/m², A4R), Multiple triple folds: 5 sheets (60-90 g/m²), 3 sheets, (91-120 g/m²)

JS-7100 Internal job collections tray: From 100 sheets, 52-300 g/m², A6R-SRA3

JS-7110 Internal shift tray: from 52-300 g/m², A6R-SRA3

HD-15: 320 GB hard drive

HD-16: 1 TB hard drive

NK-7120: Numeric keypad

UG-33 AC: ThinPrint support

UG-34 AC: Emulation (IBM Proprinter/EPSON LQ-850/LinePrinter)

USB IC Card reader: different types of card readers supported.

IB-37: Wireless Interface (USB: 5GHz/2.4GHz) with Wi-Fi Direct

IB-38: Wireless Interface (USB: 2.4GHz) with Wi-Fi Direct

IB-50: Gigabit Ethernet: 10 BaseT/100 BaseTX/1.000

IB-51: Wireless LAN Interface (802.11b/g/n)

