



4523MF, 4524MF

EFFICIENCY, SECURITY AND CARE FOR THE ENVIRONMENT

d-Copia 4523MF and d-Copia 4524MF are the A4 monochromatic, multifunctional machines offering **45 pages per minute**, ideal for dynamic, medium and large-sized work groups, as well as for remote work.

Workflows have been simplified, thanks in part to an elegant and intuitive user interface which offers a simple and fluid user experience. Thanks to the **simultaneous multiple domain** option integrated into the scanner, it is easier to digitalise and forward many electronic documents.

The ample mobile connectivity and safety provided by the **Data Security Kit**, which comes already built into the machine and can be activated with the installation of an optional storage device, ensure excellent performances and reliability, guaranteeing the kind of operational flexibility which is indispensable in the everyday routine of the modern office.

The long-lasting components and **modest energy consumption** help to satisfy environmental requirements, as well as **saving on management costs**.

Multifunction Digital Systems

| | |
|-------------------------|--|
| ECO-FRIENDLY | |
| QUALITY | |
| SPEED | |
| SECURITY | |
| COMPACT | |
| WI-FI AND WI-FI DIRECT* | |

* optional



TECHNICAL SPECIFICATIONS

GENERAL

Type: Desk Printer/Scanner/Copier. Fax (only d-Copia 4524MF)

Technology: Black and white laser

Print/copy speed (per minute): up to 45 A4 ppm

Duplex print/copy speed (per minute): up to 22.5 A4 ppm

Processor: ARM Cortex-A53 Dual Core 1.4GHz **Resolution:** 1200 x 1200 dpi (printing); 600 x 600 dpi (scanning/copying)

Operation panel: 21-character, 5-row LCD **Warm-up time:** 16 seconds maximum

First print out time: 5.3 seconds max.

First copy out time from DP: 6 seconds max. **First copy out time from glass:** 7 seconds max. **Memory:** Standard 1.5 GB; max. 3.5 GB (optional) **Standard interfaces:** USB 2.0 (Hi-Speed),

1 USB Host Interface, Gigabit Ethernet (10BaseT/100BaseTX/1000BaseT), Wireless LAN optional (IEEE 802.11b/g/n), 1 eKUIO slot for optional internal print server or SSD hard disk, optional slot for SD card

Built-in counter: 100 department codes

Duty cycle (pages/month): 15,000

Dimensions (L x D x H): 475 mm x 476 mm x 575 mm

Weight: approx. 22.3 kg (excluding toner)

Power supply: AC 220 V ~ 240 V, 50/60 Hz

Energy consumption while printing/copying: d-Copia 4523MF: 584.7 W/601.6 W;

d-Copia 4524MF: 594.1 W/606 W

Energy consumption in ready mode:

d-Copia 4523MF: 54.9 W;

d-Copia 4524MF: 55.9 W

Energy consumption in stand-by:

d-Copia 4523MF: 0.5 W;

d-Copia 4524MF: 0.6 W

Noise levels

(sound pressure level **ISO 7779/ISO 9296**): during

printing: 54 dB(A) LpA

in stand-by: 30 dB(A) LpA

TEC (Typical Electricity Consumption): 0.61 kWh/ week

Safety standards: TÜV/GS, CE

These products are manufactured by a company that operates in accordance with ISO 9001 quality standards and ISO 14001 environmental standards.

PAPER HANDLING

All paper capacities shown are based on a maximum paper thickness of 0.11mm under normal environmental conditions.

Multi-use bypass: 100 sheets, 60-220 g/m², A4, A5, A6, B5, B6, Letter, Legal, Folio, Custom (70x140 mm - 216x356 mm), paper for banners up to 915 mm

Standard tray: for 500 sheets, 60-120 g/m², A4, A5, B5, Letter, Legal, Folio, Custom (140x210 mm - 216x356 mm)

Optional PF-3110 tray:

max 500 sheets, 60-120 g/m², A4, A5, B5, Letter, Legal, Custom (92x162 mm - 216x356 mm) (max 4 additional trays)

Maximum input paper capacity:

2,600 A4 sheets (with additional trays) **Reversing automatic document feeder:** 75-sheet RADF, 50-120 g/m², A4, A5, B5, Letter, Legal, Custom (105x148 mm - 216x356 mm)

Output paper capacity: 250 sheets face down

Standard duplex function: 60-120 g/m², A4, A5, B5, Letter, Legal, Custom (140x210 mm - 216x356 mm)

PRINT FUNCTION

Print speed per minute: up to 45 A4 ppm

Emulations: PCL 6 (5c/XL), KPDL 3 (PostScript 3 compatible), PDF Direct Print, XPS Direct Print, AES, Direct Print TIFF/JPEG, Open XPS, URF, PWG Raster, PCLm, Line Printer, IBM Proprinter, Epson LQ-850

Operating systems: All current Windows operating systems, Mac OS X 10.9 or later, Chrome OS, Linux

Fonts/barcodes: 93 scalable fonts (PCL6/KPDL3); 4 fonts (Calibri); 4 fonts (Cambria); 1 Bitmap font; 45 types of one-dimensional barcodes and 1 type of two-dimensional barcode (PDF417)

Mobile printing supported: Olivetti Mobile Print for iOS and Android, AirPrint®, Wi-Fi Direct® (optional)

Print functions: Direct PDF printing, IPP 1.0 internet printing, email printing, WSD printing, secure IPP printing via TLS, local and network authentication, IPsec network data encryption, HTTPS, LDAP via TLS, SNMPv3, SMTP via TLS, POP via TLS, encrypted direct PDF printing, printing for Chrome OS

COPY FUNCTION

Max copy speed: 45 x A4 ppm

Max format of original: A4, Legal

Continuous copying: 1-999

Zoom: 25-400 % with increments of 1 %

Predefined magnification ratios: 7 reductions/5 magnifications

Image adjustment: Text + photo, photo, text, diagram/map, printed document

Other functions: Electronic collation, identity card copying, 2-in-1, 4-in-1, automatic tray selection, blank page removal

SCAN FUNCTION

Features: Scan-to-Email, Scan-to-FTP, Scan-to-SMB, Scan to USB Host, Network TWAIN, WIA, WSD scan, scanning on Chrome OS, AirPrint®

Scan speed:

one side only: 60 ipm (300 dpi, A4, B&W), 40 ipm (300 dpi, A4, colour);

duplex: 26 ipm (300 dpi, A4, B&W), 17 ipm (300 dpi, A4, colour)

Scan resolution: 600 dpi, 400 dpi, 300 dpi, 200 dpi, 256-level grey scale

Maximum scan format: A4, Legal

Identifying originals: Text, photo, text + photo, light text/fine lines, optimised for OCR

File types: TIFF/JPEG, XPS, Open XPS, PDF, PDF/A, PDF/A-1a/b, PDF/A-2a/b/u, encrypted PDF, high compression PDF

Other features: Banner scanning, colour scanning, integrated address book, Active Directory, encrypted data transfer, simultaneous multiple domains (email, fax, SMB/FTP folder, print), skip blank page

FAX FUNCTION (ONLY D-COPIA 4524MF)

Compatibility: Super G3

Modem speed: 33.6 kbps max.

Transmission time: 3 seconds max.

Scan speed: 2 seconds max.

Resolution: Normal 200x100 dpi, Fine 200x200 dpi, Superfine 200x400 dpi, Ultrafine 400x400 dpi

Max. format of original: A4/Legal **Compression method:** JBIG, MMR, MR, MH **Address book:** 200 contacts

Multiple transmission: up to 100 recipients

Received memory: 256 pages or more

Other features: Network fax, duplex transmission and reception, encrypted transmission and reception, polling transmission and reception, broadcast

CONSUMABLES

The average life of the toner cartridges complies with ISO/IEC 19752.

Black toner cartridge (B1446): up to 12,500 A4 pages (initial toner up to 6,000 pages)

Maintenance kit (B1449): up to 300,000 pages

Maintenance kit for document feeder (B1144): up to 200,000 pages

OPTIONS

Paper tray (B3928): PF-3110 x 500 sheets (max 4 additional trays)

CB-365 L (B3687): Cabinet with paper compartment (low) 38 cm x 41 cm x 25 cm

CB-360 H (B3686): Cabinet with paper compartment (high) 38 cm x 41 cm x 51 cm **CA-**

3100 (B2331): Caster kit, unit with casters for added stability. Mandatory when installing 4 optional paper feed trays

Memory expansions: MM-20 (1GB)/MM-21 (2GB), DDR3-144pin DIMM

HD-17 (B2323): 64 GB SSD hard disk

HD-18 (B2324): 256 GB SSD hard disk

HD-19 (B2325): 512 GB SSD hard disk

IB-37 (B2215): Wireless LAN (802.11b/g/n) with Wi-Fi Direct®: 2.4-GHz and 5-GHz

IB-38 (B2216): Wireless LAN (802.11b/g/n) with Wi-Fi Direct®: 2.4-GHz

IB-53 (B2341): Gigabit Ethernet Board 10 BaseT/100 BaseTX/1000 BaseT

IB-54 (B2342): Wireless network interface (802.11b/g/n): 2.4-GHz and 5-GHz

IB-55 (B2343): Wireless network interface (802.11b/g/n): 2.4-GHz

Scan Extension Kit (A) (B4498): Searchable PDF scanning (integrated OCR), MS Office (docx, xlsx, pptx). Requires HD or optional SD card

UG-33 (B8403): ThinPrint

UG-50 (B2326): TPM (Trusted Platform Module)

USB IC-Card reader + Card Authentication kit (B) - (B8237): Supports various types of card/badge authentication/reading

Card Reader Holder 10 (B4845): Plastic support to integrate the badge reader into the control panel