


High quality, low cost

The ECOSYS MA2600cfx/MA2600cwfx enhances productivity with mobile printing capabilities and major cloud connectivity. Offering users an improved user experience with a colour touchscreen and dual scan document processor, this desktop A4 MFP will elevate your processes.



ECOSYS MA2600cfx/MA2600cwfx

Print speeds up to 26 ppm

Compact design, low-noise printing

Updated 4.3" touch panel

Specifications

GENERAL

KYOCERA ECOSYS Laser Colour Multifunctional

Operation panel: Colour 4.3 InchTFT

Type: Desktop

Engine speed:

Up to 26 A4 pages per minute simplex (single-sided),

Up to 13 A4 pages per minute duplex (both sides)

Resolution: 1200 x 1200 dpi (print),

600 x 600 dpi (scan/copy)

Recommended Print Volume:

Average 900 images per month

Maximum Print Volume: 65,000 pages per month

Maximum Life: 100,000 pages or 5 years

Recommended Scan Volume:

Average 830 pages per month

Warm-up time: Approx. 29 seconds or less (after switching on)

Time to first print: Approx. 9.5/10.5 seconds or less b/w/colour

Time to first copy: Approx. 11/13 seconds or less b/w/colour (DP), Approx. 8/10 seconds or less b/w/colour (Platen)

CPU: ARM Cortex-A53 single core 1.0GHz

Memory: Standard 1 GB

Standard interfaces: USB 2.0 (Hi-Speed), Network (10BASE-T/100BASE-TX/1000BASE-T), WLAN (802.11a/b/g/n/ac, Wi-Fi Direct, 2.4/5 GHz)², USB host for USB flash memory, IC Card Reader, slot for optional SD/SDHC card

Integrated accounting: 20 department codes

Dimensions (W x D x H):

Without packaging: 410 x 416 x 457 mm,

With packaging: 596 x 571 x 599mm

Weight: Without packaging:

Approx. 26 kg (with bundled toner)

Approx. 26 kg (without bundled toner)

With packaging: 33 kg

Power source: AC 220 ~ 240 V, 50/60 Hz

Power consumption:

Printing/Copying: 375 W

Ready mode: 41 W

Sleep-mode: 0.4 W

Noise (sound pressure level: ISO 7779/ISO 9296):

Copying/Printing: 49 dB (A)

Quiet mode: 44 dB (A)

Stand-by: 30 dB (A)

Safety standards: TÜV/GS, CE

This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

PAPER HANDLING

All paper capacities quoted are based on paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.

Input capacity: Multi-purpose tray: 50 sheets, 60–220 g/m², A6, A5, A4, custom (70 × 148 – 216 × 356 mm),

Standard universal paper cassette: 250 sheets, 60–163 g/m², A6, A5, A4, custom (100 × 148 – 216 × 356 mm),

Max. input capacity with options: 550 sheets.

Duplex: Standard duplex unit, two-sided printing,

60–120 g/m², A5, A4, custom (140 × 210 – 216 × 356 mm).

Document Processor: max. 50 originals, duplex scan,

60–90 g/m², A6, A5, A4, custom (100 × 148 – 216 × 356 mm)

Output capacity: Max. 150 sheets (face-down) with paper full detection

Operating systems: All current Windows operating systems, MAC OS X Version 10.9 or higher, Chrome OS, as well as other operating systems on request

Fonts/barcodes: 93 outline fonts (PCL6, KPDL3), 4

fonts (Calibri), 4 fonts (Cambria), 1 Bimap font, 45 one-

dimensional barcodes (e.g. EAN-8, EAN-13, EAN-128), as

well as support for two-dimensional barcodes PDF417 under

PRESCRIBE (PCL and other barcodes available an option)

Print features: "Proof and hold", Job storage³, Quick

copy³, Private print³, Data storage method with PIN code

or password³, Internet printing IPP 1.0, E-mail printing,

WSD Print, EcoPrint - toner save mode, AirPrint, Mopria,

Microsoft Universal Print, Job batch output, Kyocera Image

Refinement, Pull print, VPSX, IPP PIN Print, Kyocera Cloud

Access, optional Kyocera Cloud Print and Scan, Secure

Boot, Run-time Integrity Check, Allowlisting, TLS 1.3,

IPSec, HTTPS, SNMPv3, S/MIME, encrypted PDF direct

printing, Security Watermark, electronic PDF signature,

IPP over TLS, WSD, local and network authentication,

Windows authentication (NTLM v2, Kerberos), Restriction

of the user group through user login administration, IP

filtering, port number restriction, blocking of interfaces,

Security Quick Setup, Administrator Authentication on

Firmware Update, SIEM Support (SysLog), SCEP, OCSP/

CRL, optional TPM (Trusted Platform Module)

Mobile printing support: KYOCERA Mobile Print app for

iOS and Android, AirPrint, Mopria, Microsoft Universal Print,

Wi-Fi Direct⁴

FAX FUNCTIONS

Compatibility: Super G3

Modern speed: Max. 33.6 kbps

Transmission speed: Max. 3 seconds (JBIG)

Scanning speed: 2 seconds or less

Address book: 300 entries

Scanning density:

Normal: 8 dot/mm x 3.85 line/mm (200 x 100 dpi)

Fine: 8 dot/mm x 7.7 line/mm (200 x 200 dpi)

Superfine: 8 dot/mm x 15.4 line/mm (200 x 400 dpi)

Ultrafine: 16 dot/mm x 15.4 line/mm (400 x 400 dpi)

Halftone: 256 grey scales

Maximum original size: A4/Legal

Compression method: JBIG, MMR, MR, MH

Memory reception: 256 sheets or more

Features: Network Fax, Memory Reception, Fax Polling,

Duplex Receive, Multiple Scan, Fax Forwarding, Fax Direct,

Scheduled transmission, Sub address, Fax dedicated paper

source, Shared Fax Driver, text readability improvement

<